APPENDIX A.6 BIOSCREEN EXAMPLES

Example 1: SWMU 66, Keesler AFB, Mississippi

- Input Data
- Fig. 1 Source Map
- BIOSCREEN Modeling Summary
- Fig. 2 BIOSCREEN Input Data
- Fig. 3 BIOSCREEN Centerline Output
- Fig. 4 BIOSCREEN Array Output


Example 2: UST Site 870, Hill AFB, Utah

- Input Data
- Fig. 5 Source Map
- BIOSCREEN Modeling Summary
- Fig. 6 BIOSCREEN Input Data
- Fig. 7 BIOSCREEN Centerline Output
- Fig. 8 BIOSCREEN Array Output

BIOSCREEN EXAMPLE 1

Keesler Air Force Base, SWMU 66, Mississippi

DATA TYPE	Parameter	Value	Source of Data
Hydrogeology	 Hydraulic Conductivity: Hydraulic Gradient: Porosity:	1.1 x 10 ⁻² (cm/sec) 0.003 (ft/ft) 0.3	Slug-tests results Static water level measurements Estimated
Dispersion	Original: • Longitudinal Dispersivity: • Transverse Dispersivity: • Vertical Dispersivity: After Calibration:	13.3 (ft) 1.3 (ft) 0 (ft)	Based on estimated plume length of 280 ft and Xu/Eckstein relationship
	 Longitudinal Dispersivity: Transverse Dispersivity: Vertical Dispersivity: 	32.5 (ft) 3.25 (ft) 0 (ft)	Based on calibration to plume length (Note this is well within the observed range for long. dispersivity; see Fig. A.1 in Appendix A3. Remember to convert from feet to meters before using the chart).
Adsorption	• Retardation Factor:	1.0	• Calculated from R = 1+Koc x foc x b/n
	 Soil Bulk Density b: foc: Koc:	1.7 (kg/L) 0.0057% B: 38 T: 135 E: 95 X: 240	 Estimated Lab analysis Literature - use Koc = 38
Biodegradation	Background Conc. (mg/L): Minimum Conc. (mg/L): Change in Conc. (mg/L): Electron Acceptor:	O2 NO3 SO4 2.05 0.7 26.2 - 0.4 - 0 - 3.8 1.65 0.7 22.4	Based on March 1995 groundwater sampling program conducted by Groundwater Services, Inc.
	Max. Conc. (mg/L): Avg. Conc. (mg/L):	36.1 7.4 16.6 6.6 Note: Boxed values are BIOSCREEN input values.	
General	 Modeled Area Length: Modeled Area Width: Simulation Time:	320 (ft) 200 (ft) 6 (yrs)	Based on area of affected groundwater plume Steady-state flow
Source Data	• Source Thickness: • Source Concentration:	10 (ft) (See Figure 1)	Based on geologic logs and lumped BTEX monitoring data
Actual Data	Distance From Source (ft): BTEX Conc. (mg/L):	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	Based on observed concentrations at site
OUTPUT	Centerline Concentration:	See Figure 3	
	Array Concentration:	See Figure 4	



BIOSCREEN Modeling Summary, Keesler Air Force Base, SWMU 66, Mississippi:

- BIOSCREEN was used to try to reproduce the movement of the plume from 1989 (the best guess for when the release occurred) to 1995.
- The soluble mass in soil and NAPL was estimated by integrating BTEX soil concentrations contours mapped as part of the site soil delineation program. An estimated 2000 Kg of BTEX was estimated to be present at the site. This value represented a source half-life of 60 years with the instantaneous reaction model (the first value shown in the source half-life box in Figure 2), a relatively long half-life, so the 2000 Kg measured in 1995 was assumed to be representative of 1989 conditions.
- The instantaneous reaction model was used as the primary model to try to reproduce the plume length (~ 280 ft).
- Because a decaying source was used, the source concentration on the input screen (representing concentrations 6 yrs ago) were adjusted so the source concentration on the centerline output screen (representing concentrations now) were equal to 12 mg/L. Because the source decay term is different for the first order decay and instantaneous reaction models, this simulation focused on matching the instantaneous reaction model. The final result was a source concentration of 13.68 mg/L in the center of the source zone (note on the centerline output the source concentration is 12.021 mg/L).
- The initial run of the instantaneous reaction model indicated that the plume was too long. This indicates that there is more mixing of hydrocarbon and electron acceptors at the site than is predicted by the model. Therefore the longitudinal dispersivity was adjusted upwards (more mixing) until BIOSCREEN matched the observed plume length. The final longitudinal dispersivity was 32.5 ft.
- As a check the first-order decay model was used with the BIOSCREEN default value of 2 yrs. This run greatly overestimated the plume length, so the amount of biodegradation was increased by decreasing the solute half-life. A good match of the plume was reached with a solute half-life of 0.15 years.
- As shown in Figure 3, BIOSCREEN matches the observed plume fairly well. The instantaneous model is more accurate near the source while the first order decay model is more accurate near the middle of the plume. Both models reproduce the actual plume length relatively well.
- As shown in Figure 4, the current plume is estimated to contain 7.8 kg of BTEX. BIOSCREEN indicates that the plume under a no-degradation scenario would contain 126.3 kg BTEX. In other words BIOSCREEN indicates that 94% of the BTEX mass that has left the source since 1989 has biodegraded.
- Most of the source mass postulated to be in place in 1989 is still there in 1996 (2000 kg vs. 1837 kg, or 92% left).
- The current plume contains 1.0 ac-ft of contaminated water, with 1.019 acre-ft/yr of water being contaminated as it flows through the source. Because the plume is almost at steady state, 1.019 ac-ft of water become contaminated per year with the same amount being remediated every year due to in-situ biodegradation and other attenuation processes.

BIOSCREEN User's Manual June 1996




Figure 2. BIOSCREEN Input Screen. Keesler Air Force Base, Mississippi.




Figure 3. Centerline Output. Keesler Air Force Base, Mississippi.





Figure 4. Array Concentration Output. Keesler Air Force Base, Mississippi. EXAMPLE 2

Hill Air Force Base, UST Site 870, Utah

DATA TYPE	Parameter	Value	Source
Hydrogeology	 Hydraulic Conductivity: Hydraulic Gradient: Porosity:	8.05 x 10 ⁻³ (cm/sec) 0.048 (ft/ft) 0.25	Slug-tests results Static water level measurements Estimated
Dispersion	Original • Longitudinal Dispersivity: • Transverse Dispersivity: • Vertical Dispersivity:	28.5 (ft) 2.85 (ft) 0 (ft)	 Based on estimated plume length of 1450 ft and Xu's dispersivity formula Note: No calibration was necessary to match the observed plume length.
Adsorption	• Retardation Factor:	1.3	• Calculated from R = 1+Koc x foc x b/n
	 Soil Bulk Density b: foc: Koc:	1.7 (kg/L) 0.08% B: 38 T: 135 E: 95 X: 240	 Estimated Lab analysis Literature - use Koc = 38
Biodegradation	Electron Acceptor: Background Conc. (mg/L): Minimum Conc. (mg/L): Change in Conc. (mg/L): Electron Acceptor: Max. Conc. (mg/L): Avg. Conc. (mg/L):	O2 NO3 SO4 6.0 17.0 100 - 0.22 - 0 - 0 5.78 17.0 100 Fe CH4 50.5 2.04 11.3 0.414 Note: Boxed values are BIOSCREEN input values.	Based on July 1994 groundwater sampling program conducted by Parsons Engineering Science, Inc.
General	 Modeled Area Length: Modeled Area Width: Simulation Time:	1450 (ft) 320 (ft) 5 (yrs)	Based on area of affected groundwater plume Steady-state flow
Source Data	• Source Thickness: • Source Concentration:	10 (ft) (See Figure 5)	Based on geologic logs and lumped BTEX monitoring data
Actual Data	Distance from Source (ft): BTEX Conc. (mg/L):	340 1080 1350 1420 8.0 1.0 0.02 0.005	Based on observed concentration contour at site (see Figure 5)
OUTPUT	Centerline Concentration:	See Figure 7	, ,
	Array Concentration:	See Figure 8	



BIOSCREEN Modeling Summary Hill Air Force Base, UST Site 870, Utah:

- BIOSCREEN was used to try to reproduce the movement of the plume.
- An infinite source was assumed to simplify the modeling scenario. The source was assumed to
 be in the high concentration zone of the plume area (see Figure 5). Note that the zone of
 affected soil was quite large; however much of the affected soil zone downgradient of the
 source was relatively low concentration.

Two modeling approaches could be applied: 1) assuming the source zone is just downgradient of the affected soil area (near well EPA-82-C) and ignoring the area upgradient of the this point, and 2) modeling most of the plume with source near MW-1. Alternative 1 is theoretically more accurate, as BIOSCREEN cannot account for the contributions from any affected soil zone downgradient of the source. At the case of Hill AFB, however, it was assumed that the contributions from this downgradient affected soil were relatively minor and that the main process of interest was the length of the plume from the high-concentration source zone. Therefore Alternative 2 was modeled, with the note that the middle of the actual plume may actually have higher concentrations than would be expected due to the contaminants in the downgradient affected soil zone.

- The instantaneous reaction model was used as the primary model to try to reproduce the plume length (\sim 280 ft) as shown in Figure 7.
- The initial run of the instantaneous reaction model reproduced the existing plume without any need for calibration of dispersivity.
- As a check the first-order decay model was used with the BIOSCREEN default value of 2 yrs. This run greatly overestimated the plume length, so the amount of biodegradation was increased by decreasing the solute half-life. A half-life value of 0.1 years was required to match the plume length, although the match in the middle in the plume was much poorer.
- As shown in Figure 7, BIOSCREEN matches the observed plume fairly well. The
 instantaneous model is more accurate near the source while the first order decay model is
 more accurate near the middle of the plume. Both models reproduce the actual plume
 length relatively well.
- As shown in Figure 8, the model was unable to calculate the mass balances. A quick evaluation shows the reason: with a seepage velocity of 1609 ft/yr and a 5 year simulation time, the undegraded plume should be over 8000 ft long. Because the mass balance is based on a comparison of a complete undegraded plume vs. a degraded plume, a model area length of 8000 ft would be required for BIOSCREEN to complete the mass balance calculation. Therefore two runs would be needed to complete the simulation: 1) a run with a modeled length of 1450 feet to calibrate and evalute the match to existing data, and 2) a run with a modeled length of 8000 ft to do the mass balance. The results of the second run (change of model area length from 1450 ft to 8000 ft) indicate that over 99% of the mass that has left the source has biodegraded by the time groundwater has traveled 1450 ft.




Figure 6. BIOSCREEN Input Screen. Hill Air Force Base, Utah.




Figure 7. Centerline Output. Hill Air Force Base, Utah.




Figure 8. Array Concentration Output. Hill Air Force Base, Utah.